

Decorative Stamped wall coating

USES

METOPRES WALL is impermeable mortar can be colored with excellent adherence to most types of wall.

METOPRES WALL is a decorative wall coating that fills cracks and prevents moisture intrusion on exterior wall surfaces, prolonging the life of a building.

METOPRES WALL Ready-To-Use, that can be applied to numerous different substrates to provide a Beautiful decorative Water coating

Thickness of coatings can vary between few millimeters to few cm according to the chosen design.

ADVANTAGES

- *Durable , **METOPRES WALL** coating long lasting.
- *Easy to clean
- *Economical to use.
- *Versatile, can be applied on most concrete surfaces, Indoor and outdoor
- *Ready-To-Use,
- *Quick rate of application
- *Availability of a large number of patterns.
- *Easy to repair.

COLOR

Standard white but can be produced coloured too.

APPLICATION FEILDS

- **METOPRES WALL** can be applied on
 - *All types of sound concrete surfaces
 - *Brick work
 - *Wood surfaces,
 - *Indoor and out door walls.

APPLICATION STEPS

Surface preparation:

*The surface must be clean, dry and in condition. Do not apply, if the surface is not in good condition.

* If the surface is new, it must be cured (e.g. 28 days for cement based walls)

*Apply bindersur 29 primer on the clean wall surface .

Instructions for use

Application of **METOPRES WALL** :

*Mix each pack (30 kg) **METOPRES WALL** with (18-22 %) water in a mixing machine. Let it rest for 5-10 minutes then apply with the aid of a trowel in the required thickness (thickness depends on the chosen texture).

*Brush liquid release agent on the surface of the textured mats.

*Place textured mat on the surface of the coating and press gently until the desired texture is achieved.

*continue these step until all the required area finished.

*Leave to cure.



Decorative Stamped wall coating

*Apply Patinax colours on the surface to give desired decorative effects.

*Apply (150-200g/m²) METOSEAL 100K or METOSEAL 205 S on the final surface and leave to dry
METOSEAL is on a dry surface .

STORAGE:

*Store in a dry , non humid area,
*No more than five bags should be stacked on top of each other,
*Shelf life: generally 6 months from production date and if properly stored this period can be as long as 1 year.

COVERAGE :

1.5 kg/mm is used in stamped concrete applications.

CAUTION:

Fire

METOPRES WALL is not flammable.

Health and safety

*It is a cementitious material so do not allow contact with acids and other corrosive chemicals,

*The above mentioned application system is for normal weather conditions (+5 - + 30) . In the case of extreme weather conditions this application method must be modified accordingly.(contact our office for advice)

*METOPRES WALL is a cementitious material and become alkaline when mixed with water therefore avoid contact with skin it can be harmful and wash thoroughly with water.

LIMITED WARRANTY

All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct also based on our long experience in this field of construction. METOP LTD. Warrants it's products (METOPRES) to be free of manufacturing defects and contains best quality ingredients. Since no control is exerted over it's application and use METOP LTD. Makes no warranty

,either expressed or implied, concerning this product.

Extra and special guaranties can be granted to certain big project by obtaining mutual agreements between concerning parties. The company detailed application instructions must be complied with for any company guaranties to be applicable.

